

RAVAPROOF AVIPGUM



DESCRIPTION

AVIP GUM is a one-component, solvent-based, watertight bituminous mastic sealant. After maturation it forms a single flexible, insoluble membrane.

PRIMARY USES

AVIPGUM is an excellent product that not only lead to great resilience even in very low temperatures (-20°C) but also combines economy and efficiency. AVIPGUM can be used to seal joints in horizontal and vertical surfaces for sealing capillaries cracks, as complementary sealant material when it is difficult to paste bitumen membranes on some surfaces (e.g. gutters, vents, etc.) and on the bonding points of the bitumen membranes. In combination with AREXOL LAC as primer, it has excellent adhesion to all structural surfaces of concrete, metal, wood etc. AVIP GUM is not affected by low concentration acid and alkaline solutions. It is though affected by solvents and it's not compatible with Polystyrene.

COMPOSTITION

AVIPGUM is made from bitumen, special polymers, binder fibers, filler, and aromatic hydrocarbons.

PACKAGING

AVIPGUM is available in metallic pails of 1kg, 5kg and 20kg.

TYPICAL PROPERTIES

Description	Bituminous Mastic Sealant
Color	Black
Odor	Characterisitic
Appearance	Pasty
Aromatics content	≤10%
Density	1300-1400 g/l
Solids content	≥90%

APPLICATION

Before application, ensure that the surface is clear and free from rotten materials, dust, oil, lubricants and other waste material. **AVIPGUM** can be applied with spatula or trowel (no thinning or heat is required). In case the joint gaps that have to be covered/filled are big and stiff, prior to application by flowing (directly from the dispenser) it must be thinned out with benzene. **AVIPGUM** is suitable for most common horizontal and vertical, small to medium joint gaps. The material obtains its final form after 24 hours. As it contains a small amount of volatiles, it presents minimal shrinkage. The dimensions of the joint gap should not be more than 2cm in width and 1.5cm of depth. Otherwise, joint filling cords should be used. The cords width must be approximately 30-40% bigger than the width of the gap and the application depth should not be more than 1,5cm. For rabbets bigger than 1cm, it is required a first layer of primer with **AREXOL LAC**. **AVIP GUM** is not recommended for application in floor joints of high traffic. In case the material is to be left exposed to direct sunlight, it is recommended to be protected with **RECTIFLEX**.

ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel.: +30 214 400 8 400

INOFYTA
Distribution Center
55th km National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 586

N.ARTAKI EVIA
Roofite Plant
Profitis Ilias
34600, N.Artaki Evia
Tel.: +30 22210 43985

ARMA VIOTIAS
Bitumen Products Plant
Stathmos
32200, Arma Viotias
Tel.: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214

Business Registered Number (GEMI): 363401000

Website: www.ravagohellas.gr

Email: info@ravagohellas.gr

RAVAPROOF AVIPGUM



CONSUMPTION

The consumption depends on the structure of the surface and the amount of the gap volume. Indicatively, for a joint of 1cm thickness, 1cm height and 1m length, the consumption would be 130-140g.

STORAGE

Use the product within two (2) years from the date of production. It should be stored indoors and at temperatures from 5-35°C. Close the package tightly after each use. If the product had been stored for a long time you can thin it out with benzene, if required.

Storage under not recommended conditions will result in deterioration of the product or packaging.

SAFETY AND HEALTH

The material is classified as dangerous according to European Regulation 1272/2008. Keep away from sparks and flames. Do not smoke. Do not inhale, avoid contact with eyes and mouth, and in case you apply it by airless spray use a mask. Do not apply in closed spaces without adequate air supply. In liquid form the material contaminates the water. Do not pour it on the ground or water. Always follow the related rules. For additional information refer to the SDS of this material. Do not dispose of the material on the ground.

The information contained in this publication of RAVAGO HELLAS SA is believed to be accurate and provided in good faith, based on our current knowledge and experience, when the products are stored, used and applied under the prescribed conditions. Nevertheless is up to the Users to satisfy the suitability of the product for their own specific purpose.



ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel.: +30 214 400 8 400

INOFYTA
Distribution Center
55th km National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 586

N.ARTAKI EVIA
Roofite Plant
Profitis Ilias
34600, N.Artaki Evia
Tel.: +30 22210 43985

ARMA VIOTIAS
Bitumen Products Plant
Stathmos
32200, Arma Viotias
Tel.: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214

Business Registered Number (GEMI): 363401000

Website: www.ravagohellas.gr

Email: info@ravagohellas.gr