RAVAPROOF AVIPRIMER W



DESCRIPTION

AVIPRIMER W is a high quality acrylic water primer ideal for all plastic and acrylic paints. It has great penetrating ability, strong adhesion and excellent insulating properties.

PRIMARY USES

AVIPRIMER W presents excellent adhesion and resistance to alkaline surfaces of concrete, plaster, chipboard, plasterboard etc. It is suitable for indoor and outdoor use.

COMPOSTITION

AVIPRIMER W is is produced from resins and special additives.

PACKAGING

AVIPRIMER W is available in 5 and 10kg plastic containers.

APPLICATION

The surface to be sealed must be clean, free of dust, grease, salts, rust, loose paint and residue and loose materials.

Dilute with water in a ratio of 1: 4 and apply with a brush or roller in one layer. Stirring is required before use. Following layer should take place after one hour. The application of the material is not suitable at temperatures below 10°C and above 35°C, in increased humidity conditions and/or rainfall.

CONSUMPTION

Consumption depends on the type of substrate and the characteristics of the intended use. Indicatively, 1L **AVIPRIMER W** is required for 30-40m².

STORAGE

Use the product within two (2) years from the date of production. It should be stored indoors and at temperatures from 5-35oC. Close the package tightly after each use.

Storage under not recommended conditions will result in deterioration of the product or packaging.

As with all chemicals, contact with eyes, mouth, skin and food should be avoided during use and storage. In case of contact with eyes and skin, use plenty of water and seek medical advice by referring label description and Safety Data Sheet. All used tools should be cleaned with water while the material is wet.

Seek medical attention immediately in case of contact with skin, eyes, or ingestion. Refer to the Safety Data Sheet for more information. The product is not classified as dangerous according to European Regulation 1272/2008.

Do not dispose of the material on the ground.

The information contained in this publication of RAVAGO HELLAS SA is believed to be accurate and provided in good faith, based on our current knowledge and experience, when the products are stored, used and applied under the prescribed conditions. Nevertheless is up to the Users to satisfy the suitability of the product for their own specific purpose.



ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel: +30.214.400.8.400

INOFYTA

Distribution Center

55th klm National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 566

N.ARTAKI EVIA Rooftile Plant Profitis Ilias 34600, N.Artaki Evia Tel.: +30 22210 43985 ARMA VIOTIAS
Bitumen Products Plan
Stathmos
32200, Arma Viotias
Tel: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214

ss Registered Number (GEMI): 363401000

RAVAPROOF AVIPrimer W

