|   | writer care solution | FILA INDUSTRIA CHIMICA S.P.A. | Revision nr. 7        |
|---|----------------------|-------------------------------|-----------------------|
|   |                      |                               | Dated 07/09/2018      |
|   |                      | SR95                          | Printed on 14/06/2019 |
|   |                      | 0                             | Page n. 1/17          |
| l |                      |                               | Replaced revision:6   |

# Safety data sheet according to regulation (CE) n. 1907/2006 (REACH), Annex II, and successive adjustments introduced by Commission Regulation (EU) no. 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **SR95** 

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Stain remover

|  |   | D ( ' '      | 0        |
|--|---|--------------|----------|
| Identified Uses  | Industrial  | Professional | Consumer |
| Uses   | ✓   | ✓            | •        |
| 1.3. Details of the supplier of the safety data sheet Name Full address District and Country | FILA INDUSTRIA CHIMICA S.<br>Via Garibaldi, 58<br>35018 San Martino di Lupari (<br>ITALIA |              |          |
|  | Tel. +39.049.9467300  |              |          |
|  | Fax +39.049.9460753   |              |          |
| e-mail address of the competent person   |   |              |          |
| responsible for the Safety Data Sheet  | sds@filasolutions.com   |              |          |
| 1.4. Emergency telephone number     For urgent inquiries refer to                            | TEL +39.049.9467300 (Monda  | y –          |          |

Friday; 8.30 - 12.30 and 14.00 - 17.30)

UNITED KINGDOM: NHS Direct 111 (In England, Scotland North Ireland) 08454647

(Wales); IRELAND 018092166


#### **SECTION 2. Hazards identification**

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| Substance or mixture corrosive to metals, category 1    | H290 | May be corrosive to metals.                      |
|---|------|--|
| Skin corrosion, category 1B                             | H314 | Causes severe skin burns and eye damage.         |
| Serious eye damage, category 1                          | H318 | Causes serious eye damage.                       |
| Hazardous to the aquatic environment, acute toxicity,   | H400 | Very toxic to aquatic life.                      |
| category 1  |      |  |
| Hazardous to the aquatic environment, chronic toxicity, | H411 | Toxic to aquatic life with long lasting effects. |



category 2

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

**H290** May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

**H400** Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects. EUH031 Contact with acids liberates toxic gas.

**EUH206** Warning! Do not use together with other products. May release dangerous gases (chlorine).

Precautionary statements:

P501 Dispose of contents / container in accordance with local/regional/national/international regulation.

P102 Keep out of reach of children.

**P260** Do not breathe dust / fume / gas / mist / vapours / spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

Contains: SODIUM HYPOCHLORITE

Less than 5% non-ionic surfactants

5% or over but less than chlorine-based bleaching agents

15%


Preservation agents

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### **SECTION 3. Composition/information on ingredients**

### 3.1. Substances



Information not relevant

#### 3.2. Mixtures

Contains:

| Identification                 | x = Conc. %       | Classification 1272/2008 (CLP)  |
|--------------------------------|-------------------|---|
| SODIUM HYPOCHLORITE            |                   |   |
| CAS 7681-52-9                  | $5 \le x < 6,5$   | Met. Corr. 1 H290, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1, EUH031, Classification note according to Annex VI to the CLP Regulation: B |
| EC 231-668-3                   |                   |   |
| INDEX 017-011-00-1             |                   |   |
| Reg. no. 01-2119488154-34      |                   |   |
| POTASSIUM CARBONATE            |                   |   |
| CAS 584-08-7                   | $3 \le x < 4$     | Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335   |
| EC 209-529-3                   |                   |   |
| INDEX -                        |                   |   |
| Reg. no. 01-2119532646-36      |                   |   |
| Sodium chlorate                |                   |   |
| CAS 7775-09-9                  | $1,5 \le x < 2,5$ | Org. Perox A H240, Ox. Liq. 1 H271, Acute Tox. 4 H302, Aquatic Chronic 2 H411   |
| EC 231-887-4                   |                   |   |
| INDEX 017-005-00-9             |                   |   |
| Reg. no. 01-2119474389-23      |                   |   |
| SODIUM HYDROXIDE               |                   |   |
| CAS 1310-73-2                  | 1 ≤ x < 2         | Met. Corr. 1 H290, Skin Corr. 1A H314, Eye Dam. 1 H318  |
| EC 215-185-5                   |                   |   |
| INDEX 011-002-00-6             |                   |   |
| Reg. no. 01-2119457892-27      |                   |   |
| N,N-Dimethyltetradecylamine N- |                   |   |
| oxide<br>CAS 3332-27-2         | 1 ≤ x < 2         | Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411  |
| EC 222-059-3                   |                   | THOO NET, Aquallo Official Z Littl  |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### **SECTION 4. First aid measures**

### 4.1. Description of first aid measures

Reg. no. 01-2119949262-37

INDEX -

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a

| softes can solution | FILA INDUSTRIA CHIMICA S.P.A. | Revision nr. 7        |
|---------------------|-------------------------------|-----------------------|
|                     |                               | Dated 07/09/2018      |
|                     | SR95                          | Printed on 14/06/2019 |
|                     | S.NOS                         | Page n. 4/17          |
|                     |                               | Replaced revision:6   |

#### doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

### 5.3. Advice for firefighters

### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.


Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.



Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

Nařízení vlády č. 361/2007 Sb. kterým se stanoví podmínky ochrany zdraví při práci

0

#### 7.3. Specific end use(s)

Information not available

### **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

Česká Republika

Regulatory References:

CZE

| DNK | Danmark        | Graensevaerdier per stoffer og materialer   |
|-----|----------------|---|
| ESP | España         | INSHT - Límites de exposición profesional para agentes químicos en España 2017  |
| FIN | Suomi          | HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveysministeriön julkaisuja 2012:5  |
| FRA | France         | JORF n°0109 du 10 mai 2012 page 8773 texte n° 102   |
| GBR | United Kingdom | EH40/2005 Workplace exposure limits   |
| GRC | Ελλάδα         | ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012   |
| HRV | Hrvatska       | NN13/09 - Ministarstvo gospodarstva, rada i poduzetništva   |
| HUN | Magyarország   | 50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról   |
| POL | Polska         | ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 7 czerwca 2017 r   |
| ROU | România        | Monitorul Oficial al României 44; 2012-01-19  |
| SVK | Slovensko      | NARIADENIE VLÁDY Slovenskej republiky z 20. júna 2007   |
| SVN | Slovenija      | Uradni list Republike Slovenije 04.06.2015 (1602) - Pravilnik o spremembah in dopolnitvah Pravilnika o<br>varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu |
|     | TLV-ACGIH      | ACGIH 2018  |
|     |                |   |

| SODIUM HYPOCHLORITE                                   |          |       |   |
|---|----------|-------|---|
| Predicted no-effect concentration - PNEC              |          |       |   |
| Normal value in fresh water                           | 0,00021  | mg/l  |   |
| Normal value in marine water                          | 0,000042 | mg/l  |   |
| Normal value for water, intermittent release          | 0,00026  | mg/l  | _ |
| Normal value of STP microorganisms                    | 4,69     | mg/l  |   |
| Normal value for the food chain (secondary poisoning) | 11,1     | mg/kg |   |
|   |          |       |   |

| Health - Derived no-effect level - DNEL / DMEL |            |  |  |  |  |  |  |  |
|--|------------|--|--|--|--|--|--|--|
| Effects on                                     | Effects on |  |  |  |  |  |  |  |
| consumers                                      | workers    |  |  |  |  |  |  |  |
|  |            |  |  |  |  |  |  |  |
|  |            |  |  |  |  |  |  |  |



# FILA INDUSTRIA CHIMICA S.P.A.

**SR95** 

Revision nr. 7

Dated 07/09/2018 Printed on 14/06/2019

Page n. 6/17 Replaced revision:6

| Route of exposure                               | Acute local           | Acute systemic | Chronic local | Chronic systemic       | Acute local         | Acute<br>systemic | Chronic local | Chronic systemic |
|---|-----------------------|----------------|---------------|------------------------|---------------------|-------------------|---------------|------------------|
| Oral  |                       |                | VND           | 0,26 mg/kg<br>bw/d     |                     |                   |               |                  |
| nhalation                                       | 3,1 mg/m3             | 3,1 mg/m3      | 1,55 mg/m3    | 1,55 mg/m3             | 3,1 mg/m3           | 3,1 mg/m3         | 1,55 mg/m3    | 1,55 mg/m3       |
| Potassium carbonate                             |                       |                |               |                        |                     |                   |               |                  |
| Health - Derived no-effec                       | Effects on            | OMEL           |               |                        | Effects on          |                   |               |                  |
| Route of exposure                               | consumers Acute local | Acute systemic | Chronic local | Chronic                | workers Acute local | Acute             | Chronic local | Chronic          |
| Inhalation                                      |                       |                | 10 mg/m3      | systemic<br>VND        |                     | systemic          | 10 mg/m3      | systemic<br>VND  |
| Skin  |                       |                | 8 mg/cm2      | VND                    |                     |                   | 16 mg/cm2     | VND              |
|   |                       |                |               |                        |                     |                   |               |                  |
| Sodium chlorate Predicted no-effect concentrati | on - PNFC             |                |               |                        |                     |                   |               |                  |
| Normal value in fresh water                     | OII - I NEO           |                |               | 1                      | mç                  | n/l               |               |                  |
| Normal value in marine water                    |                       |                |               | 1                      | mç                  |                   |               |                  |
| Normal value of STP microorg                    | anisms                |                |               | 100                    | mg                  |                   |               |                  |
| Normal value for the food chair                 |                       | ning)          |               | 100                    |                     | g/\<br>g/kg       |               |                  |
| Normal value for the terrestrial                |                       | ····ʊ/         |               | 3,33                   |                     | g/kg<br>g/kg      |               |                  |
| Health - Derived no-effec                       | -                     | OMEL           |               |                        |                     | ਤਾ •• <b>ਰ</b>    |               |                  |
| 20  | Effects on            |                |               |                        | Effects on workers  |                   |               |                  |
| Route of exposure                               | Acute local           | Acute systemic | Chronic local | Chronic                | Acute local         | Acute             | Chronic local | Chronic          |
| Oral  |                       |                | VND           | systemic<br>0,05 mg/kg |                     | systemic          |               | systemic         |
| Inhalation                                      |                       |                |               | bw/d                   | VND                 | 5 mg/m3           |               |                  |
| Skin  |                       |                |               |                        |                     |                   | VND           | 3,08 mg/kg       |
|   |                       |                |               |                        |                     |                   |               | bw/d             |
| SODIUM HYDROXIDE                                |                       |                |               |                        |                     |                   |               |                  |
| Threshold Limit Value                           | Country               | TWA/8h         |               | STEL/15min             |                     |                   |               |                  |
| Type  | Country               |                | nnm           |                        | nnm                 |                   |               |                  |
| TLV   | CZE                   | mg/m3<br>1     | ppm           | mg/m3                  | ppm                 |                   |               |                  |
| TLV   | DNK                   | 2              |               |                        |                     |                   |               |                  |
| VLA   | ESP                   | 2              |               |                        |                     |                   |               |                  |
|   |                       |                |               | 0 (0)                  |                     |                   |               |                  |
| HTP   | FIN                   |                |               | 2 (C)                  |                     |                   |               |                  |
| VLEP  | FRA                   | 2              |               | 2                      |                     |                   |               |                  |
| WEL   | GBR                   | 2              |               | 2                      |                     |                   |               |                  |
| TLV   | GRC<br>HRV            | 2              |               | 2                      |                     |                   |               |                  |
| CVI   | HKV                   |                |               | 2                      |                     |                   |               |                  |
|   |                       | 2              |               | 2                      |                     |                   |               |                  |
| AK  | HUN                   | 2              |               |                        |                     |                   |               |                  |
| GVI<br>AK<br>NDS                                | HUN<br>POL            | 0,5            |               | 1                      |                     |                   |               |                  |
| AK<br>NDS<br>TLV                                | HUN<br>POL<br>ROU     | 0,5            |               | 3                      |                     |                   |               |                  |
| AK<br>NDS                                       | HUN<br>POL            | 0,5            |               |                        |                     | INHAL             |               |                  |



TLV-ACGIH 2 (C)

Health Derived he offeet level DNEL / DME

| Health - Derived no-eff      | ect level - DNEL / I   | DMEL           |               |                     |                     |                   |               |                  |
|------------------------------|------------------------|----------------|---------------|---------------------|---------------------|-------------------|---------------|------------------|
|                              | Effects on             |                |               |                     | Effects on          |                   |               |                  |
| Route of exposure            | Acute local            | Acute systemic | Chronic local | Chronic<br>systemic | workers Acute local | Acute<br>systemic | Chronic local | Chronic systemic |
| Inhalation                   |                        |                | 1 mg/m3       | VND                 |                     | •                 | 1 mg/m3       | VND              |
| N,N-Dimethyltetradecy        | rlamine N-oxide        |                |               |                     |                     |                   |               |                  |
| Predicted no-effect concent  | ration - PNEC          |                |               |                     |                     |                   |               |                  |
| Normal value in fresh water  |                        |                |               | 0,0335              | m(                  | g/l               |               |                  |
| Normal value in marine wat   | er                     |                |               | 0,00335             | mç                  | g/l               |               |                  |
| Normal value for fresh water | er sediment            |                |               | 5,24                | m(                  | g/kg              |               |                  |
| Normal value for marine wa   | iter sediment          |                |               | 0,524               | m(                  | g/kg              |               |                  |
| Normal value for water, inte | ermittent release      |                |               | 0,0335              | m(                  | g/l               |               |                  |
| Normal value of STP micro    | organisms              |                |               | 24                  | mg                  | g/l               |               |                  |
| Normal value for the food c  | hain (secondary poisor | ning)          |               | 11,1                | mį                  | g/kg              |               |                  |
| Normal value for the terrest | rial compartment       |                |               | 1,02                | mg                  | g/kg              |               |                  |
| Health - Derived no-eff      | ect level - DNEL / I   | DMEL           |               |                     |                     |                   |               |                  |
|                              | Effects on             |                |               |                     | Effects on          |                   |               |                  |
| Route of exposure            | consumers Acute local  | Acute systemic | Chronic local | Chronic<br>systemic | workers Acute local | Acute<br>systemic | Chronic local | Chronic systemic |
| Oral                         |                        |                | VND           | 0,44 mg/kg          |                     | 0,00011110        |               | 5,5.011110       |
|                              |                        |                |               |                     |                     |                   |               |                  |

bw/d

bw/d

1,53 mg/m3

5,5 mg/kg

VND

VND

6,2 mg/m3

11 mg/kg

bw/d

#### Legend:

Skin

Inhalation

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

VND

VND

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

If the product may or must come into contact or react with acids, suitable technical and/or organisational measures should be taken to prevent the development of toxic and/or inflammable gases.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

| surface care solutions | FILA INDUSTRIA CHIMICA S.P.A. | Revision nr. 7        |
|------------------------|-------------------------------|-----------------------|
|                        |                               | Dated 07/09/2018      |
|                        | SR95                          | Printed on 14/06/2019 |
|                        | 51100                         | Page n. 8/17          |
|                        |                               | Replaced revision:6   |

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### **EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

### **SECTION 9. Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance viscous liquid
Colour transparent
Odour pungent
Odour threshold Not available

pH 13,5

Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available Flash point > 60 °C **Evaporation Rate** Not available Flammability of solids and gases not applicable Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not applicable Upper explosive limit Not applicable Vapour pressure Not available Vapour density Not available

Relative density 1,11

Solubility soluble in water

Partition coefficient: n-octanol/water Not available

Auto-ignition temperature Not available

| FAR. | FILA INDUSTRIA CHIMICA S.P.A. | Revision nr. 7        |
|------|-------------------------------|-----------------------|
|      |                               | Dated 07/09/2018      |
|      | SR95                          | Printed on 14/06/2019 |
|      | 5.100                         | Page n. 9/17          |
|      |                               | Replaced revision:6   |

Decomposition temperature Not available
Viscosity Not available
Explosive properties not applicable
Oxidising properties not applicable

9.2. Other information

VOC (Directive 2010/75/EC): 0
VOC (volatile carbon): 0

### **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

Information not available

#### 10.2. Chemical stability

The product is stable if stored in original containers at temperatures lower than the self accelerated decomposition temperature (SADT).

#### 10.3. Possibility of hazardous reactions

Information not available

#### 10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition. Avoid transferring into containers that may have been contaminated with other substances. Avoid storing close to inflammable or combustible products.

### SODIUM HYDROXIDE

Avoid exposure to: air, moisture, sources of heat.

### 10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.


#### SODIUM HYDROXIDE

Incompatible with: strong acids,ammonia,zinc,lead,aluminium,water,flammable liquids.

### 10.6. Hazardous decomposition products

Thermal decomposition can lead to the formation of explosive peroxides or other potentially hazardous substances.

### **SECTION 11. Toxicological information**



### 11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

#### **ACUTE TOXICITY**

LC50 (Inhalation) of the mixture:
Not classified (no significant component)
LD50 (Oral) of the mixture:
>2000 mg/kg
LD50 (Dermal) of the mixture:
Not classified (no significant component)

Potassium carbonate

LC50 (Inhalation) > 4,96 mg/l/4h rat

SODIUM HYDROXIDE

LD50 (Oral) 1350 mg/kg Rat

LD50 (Dermal) 1350 mg/kg Rabbit

SODIUM HYPOCHLORITE

LD50 (Oral) > 5000 mg/kg Rat

LD50 (Dermal) > 10000 mg/kg Rabbit

N,N-Dimethyltetradecylamine N-oxide

LD50 (Oral) 1064 mg/kg rat

| Surface care solutions | FILA INDUSTRIA CHIMICA S.P.A. | Revision nr. 7        |
|------------------------|-------------------------------|-----------------------|
|                        |                               | Dated 07/09/2018      |
|                        | SR95                          | Printed on 14/06/2019 |
|                        | Sinos                         | Page n. 11/17         |
|                        |                               | Replaced revision:6   |

Sodium chlorate

LD50 (Oral) > 5000 mg/kg rat

LD50 (Dermal) > 2000 mg/kg rabbit

#### SKIN CORROSION / IRRITATION

Corrosive for the skin

#### SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

## **SECTION 12. Ecological information**

This product is dangerous for the environment and highly toxic for aquatic organisms.

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment. **12.1. Toxicity** 



### FILA INDUSTRIA CHIMICA S.P.A.

**SR95** 

Revision nr. 7

Dated 07/09/2018

Printed on 14/06/2019

Page n. 12/17

Replaced revision:6

Potassium carbonate

LC50 - for Fish68 mg/l/96h Oncorhynchus mykissEC50 - for Crustacea200 mg/l/48h Daphnia pulexChronic NOEC for Fish33 mg/l Oncorhynchus mykiss

SODIUM HYDROXIDE

LC50 - for Fish 45,5 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea > 100 mg/l/48h Daphnia magna

SODIUM HYPOCHLORITE

LC50 - for Fish 0,059 mg/l/96h Oncorhynchus mykiss

EC50 - for Crustacea 0,04 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants 46 mg/l/72h Gracilaria tenuistipitata

Chronic NOEC for Fish 0,04 mg/l

N,N-Dimethyltetradecylamine N-oxide

LC50 - for Fish 2,67 mg/l/96h Pimephales promelas EC50 - for Crustacea 3,1 mg/l/48h Daphnia Magna

EC50 - for Algae / Aquatic Plants 0,19 mg/l/72h Pseudokirchnerella subcapitata

Sodium chlorate

LC50 - for Fish > 1000 mg/l/96h rainbow trout

EC50 - for Crustacea > 1000 mg/l/48h Daphnia magna

Chronic NOEC for Algae / Aquatic Plants > 1000 mg/l Skeletonema costatum

#### 12.2. Persistence and degradability

SODIUM HYDROXIDE

Solubility in water > 10000 mg/l

SODIUM HYPOCHLORITE

Solubility in water 1000 - 10000 mg/l

N,N-Dimethyltetradecylamine N-oxide

Rapidly degradable


12.3. Bioaccumulative potential

SODIUM HYPOCHLORITE

Partition coefficient: n-octanol/water -3,42

12.4. Mobility in soil

Information not available



#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### **SECTION 14. Transport information**

#### 14.1. UN number

ADR / RID, IMDG, IATA:

1791

### 14.2. UN proper shipping name

HYPOCHLORITE SOLUTION ADR / RID: IMDG: HYPOCHLORITE SOLUTION IATA: HYPOCHLORITE SOLUTION

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 8

> Class: 8 Label: 8

Label: 8

IATA: Class: 8 Label: 8

### 14.4. Packing group

ADR / RID, IMDG, Ш

IATA:

IMDG:

### Revision nr. 7 FILA INDUSTRIA CHIMICA S.P.A. FILR Dated 07/09/2018 Printed on 14/06/2019 **SR95** Page n. 14/17 Replaced revision:6

#### 14.5. Environmental hazards

ADR / RID: Environmentally

Hazardous

IMDG: Marine Pollutant

IATA: NO

For Air transport, environmentally hazardous mark is only mandatory for UN 3077 and UN 3082.

#### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80 Limited Tunnel Quantities: 5 restriction

code: (E)

Special Provision: -EMS: F-A, S-B

Limited

Quantities: 5

IATA: Cargo: Maximum

Packaging quantity: 60 L instructions:

856

Pass.: Maximum Packaging

quantity: 5 L instructions:

852

Special Instructions: A3, A803

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

IMDG:

### **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: E1

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

**Product** 

Point

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

| surface care solutions | FILA INDUSTRIA CHIMICA S.P.A. | Revision nr. 7        |
|------------------------|-------------------------------|-----------------------|
|                        |                               | Dated 07/09/2018      |
|                        | SR95                          | Printed on 14/06/2019 |
|                        | S.KOS                         | Page n. 15/17         |
|                        |                               | Replaced revision:6   |

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

### 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

SODIUM HYPOCHLORITE

POTASSIUM CARBONATE

SODIUM HYDROXIDE

Skin Irrit. 2

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Org. Perox A Organic peroxide, category A
Ox. Liq. 1 Oxidising liquid, category 1

Met. Corr. 1 Substance or mixture corrosive to metals, category 1

Acute Tox. 4 Acute toxicity, category 4

Skin Corr. 1A Skin corrosion, category 1A


Skin Corr. 1B Skin corrosion, category 1B

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin irritation, category 2



Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H240 Heating may cause an explosion.

**H271** May cause fire or explosion; strong oxidiser.

H290 May be corrosive to metals.H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH031 Contact with acids liberates toxic gas.

EUH206 Warning! Do not use together with other products. May release dangerous gases

(chlorine).

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament

|   | surface case substitions | FILA INDUSTRIA CHIMICA S.P.A. | Revision nr. 7        |
|---|--------------------------|-------------------------------|-----------------------|
|   |                          |                               | Dated 07/09/2018      |
|   |                          | SR95                          | Printed on 14/06/2019 |
|   |                          |                               | Page n. 17/17         |
|   |                          |                               | Replaced revision:6   |
| ı |                          |                               |                       |

- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Method for assessing the information referred to in Article 9 of Regulation (EC) No 1272/2008 which was used for classification purposes: Calculation method and experimental data.

Changes to previous review: The following sections were modified: 02 / 08 / 09 / 11 / 12 / 14 / 16.