

RAVAPROOF SEAL MAX

Elastomeric Acrylic Stucco



DESCRIPTION

RAVAPROOF SEAL MAX is a viscous, waterproofing acrylic based material.

USAGE

It is mainly used for sealing and water-tighting joint gaps. It can also be used for repairing cracks or abnormalities of wall plaster. It has resistance to low concentration alkali and acid solutions, high flexibility and excellent adhesion to materials such as cement, plaster, stone, wood, metal etc. **RAVAPROOF SEAL MAX** is available in white and gray color.

COMPONENTS

Acrylic copolymers and additives.

APPLICATION

The application of **RAVAPROOF SEAL MAX** is handy and quick. Before application it is recommended to clear the surface from dust, oil or old debris material. The joint's dimensions should not be bigger than 1x1cm. Otherwise joint filling cords should be used. The cords width must be at about 30-40% bigger than the width of the gap and the application depth should not be more than 1cm. Apply a first layer of primer with AVIPRIMER W at the sides of the joint-gap and then apply **RAVAPROOF SEAL MAX** with the use of spatula or trowel. In case a second layer is needed, apply after the previous layer is completely dried, without the use of primer. The material should not be used in below zero temperatures or during rainfall.

PACKAGING

RAVAPROOF SEAL MAX is available in plastic pails of 1, 5 and 15kg.

TYPICAL PROPERTIES

Description	Elastomeric Acrylic Stucco
Colour	White / Gray
Odor	Odorless
Solid content	63-65% w/w
Moisture Content	35-37% w/w
Density	1400-1500 gr/L

CONSUMPTION

The consumption depends on the structure of the surface and the amount of the volume gap. Indicatively, for a joint of 1x1x1cm, the consumption should be 140-150g of **RAVAPROOF SEAL MAX**.

STORAGE

Use the product within two (2) years from the date of production. It should be stored indoors and at temperatures between 5-35°C. Close the package tightly after each use. Agitate the product with a low spin drill before use.

Storage under not recommended conditions will result in deterioration of the product or packaging.

SAFETY AND HEALTH

As with all chemicals, contact with eyes, mouth, skin and food should be avoided during use and storage. In case of contact with eyes and skin, use plenty of water and seek medical advice by referring label description and Safety Data Sheet. All used tools should be cleaned with water while the material is wet.

Seek medical attention immediately in case of contact with skin, eyes, or ingestion. Refer to the

ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel.: +30 214 400 8 400

INOFYTA
Distribution Center
55th km National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 566

N.ARTAKI EVIA
Roof tile Plant
Profitis Ilias
34600, N.Artaki Evia
Tel.: +30 22210 43985

ARMA VIOTIAS
Bitumen Products Plant
Stathmos
32200, Arma Viotias
Tel.: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214

Business Registered Number (GEMI): 363401000

Website: www.ravagohellas.gr

Email: info@ravagohellas.gr

RAVAPROOF SEAL MAX

Elastomeric Acrylic Stucco



Safety Data Sheet for more information. The product do not require classification as dangerous according to European Regulation 1272/2008. Nevertheless it shall be labelled with the supplemental labelling elements **EUH211** "Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist." and **EUH210** "Safety Data Sheet available on request".

Do not dispose of the material on the ground.



The information contained in this publication of RAVAGO HELLAS SA is believed to be accurate and provided in good faith, based on our current knowledge and experience, when the products are stored, used and applied under the prescribed conditions. Nevertheless is up to the Users to satisfy the suitability of the product for their own specific purpose.

ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel.: +30 214 400 8 400

INOFYTA
Distribution Center
55th km National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 566

N.ARTAKI EVIA
Rooftile Plant
Profitis Ilias
34600, N.Artaki Evia
Tel.: +30 22210 43985

ARMA VIOTIAS
Bitumen Products Plant
Stathmos
32200, Arma Viotias
Tel.: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214

Business Registered Number (GEMI): 363401000

Website: www.ravagohellas.gr

Email: info@ravagohellas.gr

RAVAPROOF SEAL MAX

Elastomeric Acrylic Stucco



ATHENS
Head Office
115, Neratziotissis str., Maroussi
15124, Athens, Greece
Tel.: +30 214 400 8 400

INOFYTA
Distribution Center
55th km National Road Athens-Lamia
32011, Inofyta, Viotia
Tel.: +30 22620 32 588

N.ARTAKI EVIA
Rooftile Plant
Profitis Ilias
34800, N.Artaki Evia
Tel.: +30 22210 43985

ARMA VIOTIAS
Bitumen Products Plant
Stathmos
32200, Arma Viotias
Tel.: +30 22620 72083

INOFYTA
Metal Profiles Plant
Thessi Kokkinoxoma
32011, Inofyta Viotias
Tel.: +30 22620 56214

Business Registered Number (GEMI): 363401000

Website: www.ravagohellas.gr

Email: info@ravagohellas.gr