


Naturboard 035

March 2021



APPLICATIONS



PRODUCT DESCRIPTION

Insulation boards of Natural Mineral Wool with ECOSE® Technology for external walls. Naturboard 035 is a self-supporting natural mineral wool board offering high thermal performance for various applications, including wall linings of external walls, sandwich walls, drywall systems and ventilated façades.

TECHNICAL CHARACTERISTICS

Declared coefficient of thermal conductivity λ_D	0.035 W/mK
Reaction to fire	A1 - non-combustible material
Water vapour diffusion resistance factor μ	~1
Short term water absorption W_p	≤ 1 kg/m ²
Long term water absorption W_{lp}	≤ 3 kg/m ²

BENEFITS

- Very good thermal insulation properties
- Excellent fire resistance - Euroclass A1, non-combustible
- High sound absorption
- Ease of application
- Rigidity and mechanical strength
- Simple and easy handling

DESIGNATION CODE: MW - EN 13162 - T2 - WS - WL(P) - AFR5

DIMENSIONS AND PACKAGING

Thickness (mm)	Width (mm)	Length (mm)	pcs / packaging	m ² / packaging	packages / pallet	m ² / pallet	R Thermal resistance (m ² K/W)
50	600	1250	12	9	24	216	1,43
100	600	1250	6	4,5	24	108	2,85 **
120	600	1250	5	3,75	24	90	3,40 **

**Upon request we have the ability to provide equivalent materials under alternative trade names.

CERTIFICATES



Naturboard 035

March 2021

ADDITIONAL INFORMATION

Application

The product is intended for thermal and sound insulation, as well as for fire protection of external walls and drywall systems. Naturboard 035 can also be used in various types of sandwich walls and can be easily installed in ventilated façade systems. Its water repellent and flexible nature allows a continuous insulation application and provides maximum insulation performance.

Packaging

The product Naturboard 035 is delivered in PE heat-shrinking foil. The products must be stored in a dry place, indoors or under roof. In exceptional situations, the packages stored outdoors should be protected by watertight foil. The packages must not be placed directly on the ground.

Quality

Naturboard 035 is certified to comply with standard EN 13162 as well as with the EUCEB certificate which ensures that the product is biosoluble and not dangerous for health in accordance with European Directive 97\69\EC. Due to ECOSE Technology naturally based binder, it also possesses Eurofins Indoor Air Comfort Gold Certificate, regarding indoor Environmental Quality and Low-Emitting Materials.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

Knauf Insulation SA

10 Evipidou str.
176 74 Kallithea
Greece

sales.gr@knaufinsulation.com

Tel.: +30 211 710 7007

Fax.: +30 211 740 9480