

STAIN PROTECTOR FOR UNPOLISHED SURFACES

UNPOLISHED STONE AND AGGLOMERATES, TERRACOTTA, QUARRY TILES, CONCRETE



W68 is a water-based product that can also be applied to surfaces with residual moisture.



COVERAGE

With one litre:

Terracotta rustic Tuscan, polished 15/20 m²

Concrete, handmade, Spanish, Terracotta hollow tile, brick 7/10 m²

Stone 10/20 m²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1 litre: boxes of 12.
5 litres: boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Protect can from frost. Store at room temperature.
- Outdoor flooring must be properly laid before being treated and must satisfy all the specific requirements, including: adequate sloping, properly executed expansion joints, perfect isolation from the underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES

Storage temperature: from 5° to 30° C.
This product must be applied to surfaces with temperature between 10°C and 30°C.

WHAT IT'S FOR

- Seals and protects porous materials such as rough-finish natural stone, terracotta and concrete from oily dirt.
- Stain-proofing: it hampers the absorption of common watery and oily stains.
- Suitable for interior and exterior surfaces.
- For use on interior floors as a protective base-coat before the application of wax.
- It provides an anti-graffiti protection that prevents graffiti paint from bonding to surfaces. It speeds the cleaning process because graffiti can be easily removed.

ADVANTAGES

- Natural effect: does not alter the surface's original appearance.
- A water-based product free of hydrocarbon solvents, which makes the product more environment-friendly and drastically reduces the treatment times as it can be applied to surfaces with residual humidity.
- Does not form surface film.
- Does not alter terracotta frost resistance.
- Excellent also for concrete surfaces.
- The treated surfaces are suitable for food contact.
- This product has extremely low VOC emissions: certified by GEV and marked by EC1Plus and helps towards gaining credits for the LEED.

HOW TO USE IT

No dilution required: ready to use.

Indoor surfaces consisting of terracotta and natural stone and concrete: On a clean and dry surfaces, apply one coat of **W68** evenly, using a brush or fleece pad, while soaking the joints well. Wait 4 hours and then apply a coat of the specific finishing wax for the desired aesthetic effect (**MATT** for a natural effect, **LONGLIFE** for a glossy effect, if available for sale). With absorbent materials, apply a further coat of reinforcement wax one hour after the first coat of wax. For maintenance with satin effect, apply one coat of **SATIN**.

Outdoor surfaces consisting of terracotta, natural stone and concrete: On a clean surface, apply 2 coats of **W68** evenly, using a paintbrush or fleece pad, also soaking the joints well. Remove any excess unabsorbed product by dabbing it with a micro-fibre cloth, before the product dries.

Maintenance: diluted solution of **CLEANER PRO**.

Caution:

Carry out a patch test on a small surface area to check for any changes in colour. Do not apply the product externally if rain is forecast. Does not protect against acidic aggression.