



KELYFOS BOND

DECLARATION OF PERFORMANCE

Declaration Number: **KELYFOS BOND / 2301-01**

<i>1.Unique identification code of the product type</i>	KELYFOS BOND
<i>2.Intended use/uses</i>	General purpose mortar for fixing and reinforced covering of insulation boards (GP)
<i>3.Manufacturer</i>	RAVAGO HELLAS SMSA. Neratziotissis 115, Marousi Attica, 15124 Plant 001
<i>4.Authorised representative</i>	Not relevant
<i>5.System/s of AVCP</i>	System 4
<i>6a.Harmonised standard</i>	EN 998-1:2016
<i>Notified body/ies</i>	Not relevant
<i>6b.European Assessment Document</i>	Not relevant
<i>European Technical Assessment</i>	Not relevant
<i>Technical Assessment body</i>	Not relevant
<i>Notified body/ies</i>	Not relevant



7.Declared Performance-(s)			
Essential characteristics	Performance	Test Method	Harmonized Technical Specification
Reaction to fire	κλάση A1	EN 13501-1	EN 998-1:2016
Capillary water absorption	W2	EN 1015-18	
Water vapour permeability	μ: 15	EN 1015-19	
Adhesion	1,0 N/mm ² - FP:A	EN 1015-12	
Thermal conductivity λ_{10 dry}	0,45 W/mK (tabulated)	EN 1745	
Durability	evaluation based on provisions valid in the intended place of use of the mortar		
Dangerous substances	complies with paragraph 5.3.4		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:

Charis Kounadi

RBS Business Manager

Marousi 2/11/2023

CE MARKING

CE
RAVAGO HELLAS S.M.S.A 115, Neratziotissis str., Maroussi 15124, Athens Greece 23
EN 998-1 General purpose rendering mortar (GP) for external use DoP No.: KELYFOS BOND/2301-01
Reaction to fire: Class A1 Adhesion: 1.0 N/mm ² – FP: A Water absorption: W2 Water vapor diffusion coeff.: μ 15 Thermal conductivity: ($\lambda_{10, dry}$) 0.45 W/mK Durability (against freeze/thaw): evaluation based on provisions valid in the intended place of use of the mortar