

| | |
|---|--|
| 1. Unique identification code of the product-type: RAVATHERM XPS X 300 SB | |
| 30 mm ≤ d ≤ 40 mm | XPS - EN13164 - T1 - CS(10\Y)300 - CC(2/1,5/50)130 - DS(70,90) - DLT(2)5 - WD(V)3 - WL(T)0,7 - FTCD1 |
| 50 mm ≤ d ≤ 60 mm | XPS - EN13164 - T1 - CS(10\Y)300 - CC(2/1,5/50)130 - DS(70,90) - DLT(2)5 - WD(V)2 - WL(T)0,7 - FTCD1 |
| 80 mm ≤ d | XPS - EN13164 - T1 - CS(10\Y)300 - CC(2/1,5/50)130 - DS(70,90) - DLT(2)5 - WD(V)1 - WL(T)0,7 - FTCD1 |
| 2. Intended use/es: | Thermal Insulation for Buildings (ThIB) |
| 3. Manufacturer: | Ravago Building Solutions S.A. 2146 Luxembourg, 76-78 Rue de Merl |
| 4. Authorized representative: | - |
| 5. System/s of AVCP: | System 3 |
| 6a. Harmonised standard: | EN 13164:2012+A1:2015 |
| Notified body/ies: | FIW (0751) - LNE (0071) - CSTB (0679) - ÉMI (1415) - OFI (1085) |

| 7. Declared performance/s: | | |
|---|--|-------------|
| Essential characteristic | Symbol | Performance |
| Thermal conductivity | | |
| 30 – 120 mm | λ_d | 0,030 |
| 140 – 200 mm | λ_d | 0,031 |
| Thermal resistance | R_d | * |
| Dimensional tolerances | T | T1 |
| Compressive strength | CS(10\Y) | 300 |
| Tensile strength perpendicular to faces | TR | NPD |
| Reaction to fire | RtF | E |
| Continuous glowing combustion | | NPD |
| Long term water absorption by total immersion | WL(T) | 0,7 |
| Long term water absorption by diffusion | 30 – 40 mm | 3 |
| | 50 – 60 mm | 2 |
| | 80 – 280 mm | 1 |
| Water vapor diffusion resistance factor | MU | NPD |
| Durability of compressive strength against (compressive creep) | CC (2/1,5/50) | 130 |
| Durability of reaction to fire against heat, weathering, ageing/degradation | No change in reaction to fire properties for extruded polystyrene foam | |
| Durability of thermal resistance against heat, weathering, ageing/degradation | | |
| Thermal resistance and thermal conductivity | see above R_d and λ_d | |
| Freeze/thaw resistance after long term water absorption by diffusion | FTCD | 1 |
| Freeze/thaw resistance after long term water absorption by total immersion | FTCI | NPD |
| Dimensional stability under specified temperature and humidity conditions | DS | (70,90) |
| Deformation under specified compressive load and temperature conditions | DLT | (2) 5 |
| Release of dangerous substances to the indoor environment | | NPD |

* Thermal resistance (R_d)

| Thickness | R_d (m ² K/W) | Thickness | R_d (m ² K/W) | Thickness | R_d (m ² K/W) |
|-----------|----------------------------|-----------|----------------------------|-----------|----------------------------|
| 25 | 0,80 | 75 | 2,50 | 140 | 4,50 |
| 30 | 1,00 | 80 | 2,65 | 150 | 4,85 |
| 40 | 1,30 | 100 | 3,30 | 160 | 5,15 |
| 50 | 1,65 | 120 | 4,00 | 180 | 5,80 |
| 60 | 2,00 | 125 | 4,00 | 200 | 6,45 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the
manufacturer by:

Patrick Cabuy, Business Director

Place and date of issue:

2146 Luxembourg, 2024.01.02.

Signature



NPD – No Performance Determined

Ravatherm XPS X 300 SB DoP Version 1 20240102

Note: DoP in other languages can be obtained under: www.dop.ravatherm.com

