

|   |  |
|---|--|
| 1. Unique identification code of the product-type:<br><b>RAVATHERM XPS X 700 SL</b> |  |
| 30 mm ≤ d ≤ 40 mm   | XPS - EN13164 - T1 - CS(10\Y)700 - CC(2/1,5/50)250 - DS(70,90) - DLT(2)5 - WD(V)3 - WL(T)0,7 - FTCD1         |
| 50 mm ≤ d ≤ 60 mm   | XPS - EN13164 - T1 - CS(10\Y)700 - CC(2/1,5/50)250 - DS(70,90) - DLT(2)5 - WD(V)2 - WL(T)0,7 - FTCD1         |
| 80mm  | XPS - EN13164 - T1 - CS(10\Y)700 - CC(2/1,5/50)250 - DS(70,90) - DLT(2)5 - WD(V)1 - WL(T)0,7 - FTCD1         |
| 100 mm ≤ d  | XPS - EN13164 - T1 - CS(10\Y)700 - CC(2/1,5/50)250 - DS(70,90) - DLT(2)5 - WD(V)1 - WL(T)0,7 - FTCD1 – TR200 |
| 2. Intended use/es:   | Thermal Insulation for Buildings (ThIB)  |
| 3. Manufacturer:  | <b>Ravago Building Solutions S.A.</b><br>2146 Luxembourg, 76-78 Rue de Merl                                  |
| 4. Authorized representative:   | -  |
| 5. System/s of AVCP:  | System 3   |
| 6a. Harmonised standard:  | EN 13164:2012+A1:2015  |
| Notified body/ies:  | FIW (0751) - LNE (0071) - CSTB (0679) - ÉMI (1415) -OFI (1085)   |

| 7. Declared performance/s:  |  |             |
|---|--|-------------|
| Essential characteristic  | Symbol   | Performance |
| Thermal conductivity  |  |             |
|   | $\lambda_d$  | 0,031       |
| Thermal resistance  |  |             |
|   | $R_d$  | *           |
| Dimensional tolerances  | T  | T1          |
| Compressive strength  | CS(10\Y)   | 700         |
| Tensile strength perpendicular to faces                                       | 30 – 80 mm   | TR          |
|   | 100 – 240 mm   |             |
| Reaction to fire  | RtF  | E           |
| Continuous glowing combustion   |  | NPD         |
| Long term water absorption by total immersion                                 | WL(T)  | 0,7         |
| Long term water absorption by diffusion                                       | 30 – 40 mm   | WD(V)       |
|   | 50 – 60 mm   |             |
|   | 80 – 240 mm  |             |
| Water vapor diffusion resistance factor                                       | MU   | NPD         |
| Durability of compressive strength against (compressive creep)                | CC (2/1,5/50)  | 250         |
| Durability of reaction to fire against heat, weathering, ageing/degradation   | No change in reaction to fire properties for extruded polystyrene foam |             |
| Durability of thermal resistance against heat, weathering, ageing/degradation |  |             |
| Thermal resistance and thermal conductivity                                   | see above $R_d$ and $\lambda_d$  |             |
| Freeze/thaw resistance after long term water absorption by diffusion          | FTCD   | 1           |
| Freeze/thaw resistance after long term water absorption by total immersion    | FTCI   | NPD         |
| Dimensional stability under specified temperature and humidity conditions     | DS   | (70,90)     |
| Deformation under specified compressive load and temperature conditions       | DLT  | (2) 5       |
| Release of dangerous substances to the indoor environment                     |  | NPD         |

\* Thermal resistance ( $R_d$ )

| Thickness | $R_d$ (m <sup>2</sup> K/W) | Thickness | $R_d$ (m <sup>2</sup> K/W) | Thickness | $R_d$ (m <sup>2</sup> K/W) |
|-----------|----------------------------|-----------|----------------------------|-----------|----------------------------|
| 40 mm     | 1,25                       | 100 mm    | 3,20                       | 180 mm    | 5,80                       |
| 50 mm     | 1,60                       | 120 mm    | 3,85                       | 200 mm    | 6,45                       |
| 60 mm     | 1,90                       | 125 mm    | 4,00                       | 220 mm    | 7,05                       |
| 75 mm     | 2,40                       | 140 mm    | 4,50                       | 240 mm    | 7,70                       |
| 80 mm     | 2,55                       | 160 mm    | 5,15                       |           |                            |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the  
manufacturer by:

Patrick Cabuy, Business Director

Place and date of issue:

2146 Luxembourg, 2024.01.02.

Signature



NPD – No Performance Determined

Ravatherm XPS X 700 SL DoP Version 1 20240102

Note: DoP in other languages can be obtained under: [www.dop.ravatherm.com](http://www.dop.ravatherm.com)

