

1. Unique identification code of the product-type: RAVATHERM XPS X LB	
XPS - EN13164 - T3 - CS(10\Y)300 - DS(70,90) - WL(T)1,5 – TR600 – SS250	
2. Intended use/es:	Thermal Insulation for Buildings (ThIB)
3. Manufacturer:	Ravago Building Solutions S.A. 2146 Luxembourg, 76-78 Rue de Merl
4. Authorized representative:	-
5. System/s of AVCP:	System 3
6a. Harmonised standard: Notified body/ies:	EN 13164:2012+A1:2015 FIW (0751) - LNE (0071) - CSTB (0679)

7. Declared performance/s:		
Essential characteristic	Symbol	Performance
Thermal conductivity		
20 – 59 mm	λ_d	0.030
60 – 165 mm	λ_d	0.031
Thermal resistance	R_d	*
Dimensional tolerances	T	T3
Compressive strength	CS(10\Y)	300
Tensile strength perpendicular to faces	TR	600
Shear strength	SS	250
Reaction to fire	RtF	E
Continuous glowing combustion		NPD
Long term water absorption by total immersion	WL(T)	1,5
Long term water absorption by diffusion	WD(V)	NPD
Water vapor diffusion resistance factor	MU	NPD
Durability of compressive strength against (compressive creep)	CC (2/1,5/50)	NPD
Durability of reaction to fire against heat, weathering, ageing/degradation	No change in reaction to fire properties for extruded polystyrene foam	
Durability of thermal resistance against heat, weathering, ageing/degradation		
Thermal resistance and thermal conductivity	see above R_d and λ_d	
Freeze/thaw resistance after long term water absorption by diffusion	FTCD	NPD
Freeze/thaw resistance after long term water absorption by total immersion	FTCI	NPD
Dimensional stability under specified temperature and humidity conditions	DS	(70,90)
Deformation under specified compressive load and temperature conditions	DLT	NPD
Release of dangerous substances to the indoor environment		NPD

* Thermal resistance

T	0	1	2	3	4	5	6	7	8	9
20	0.65	0.70	0.70	0.75	0.80	0.80	0.85	0.90	0.90	0.95
30	1.00	1.00	1.05	1.10	1.10	1.10	1.20	1.20	1.25	1.30
40	1.30	1.35	1.40	1.40	1.45	1.45	1.50	1.55	1.60	1.60
50	.65	1.70	1.70	1.75	1.80	1.75	1.85	1.90	1.90	1.95
60	1.95	1.95	2.00	2.00	2.05	2.05	2.10	2.15	2.15	2.20
70	2.25	2.25	2.30	2.35	2.35	2.40	2.45	2.45	2.50	2.50
80	2.60	2.60	2.60	2.65	2.70	2.70	2.75	2.80	2.80	2.85
90	2.90	2.90	2.95	3.00	3.00	3.05	3.05	3.10	3.15	3.15
100	3.20	3.25	3.25	3.30	3.35	3.35	3.40	3.45	3.45	3.50
110	3.55	3.55	3.60	3.60	3.65	3.70	3.70	3.75	3.80	3.80
120	3.85	3.90	3.90	3.95	4.00	4.00	4.05	4.05	4.10	4.15
130	4.20	4.20	4.20	4.25	4.30	4.35	4.35	4.40	4.45	4.45
140	4.50	4.50	4.50	4.60	4.60	4.65	4.70	4.70	4.75	4.80
150	4.80	4.85	4.90	4.90	4.95	5.00	5.00	5.05	5.05	5.10
160	5.15	5.15	5.20	5.25	5.25	5.30	5.35	5.35	5.40	5.45

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Patrick Cabuy, Business Director

Place and date of issue:

2146 Luxembourg,
203.1024.01.02.

Signature



NPD – No Performance Determined

Note : DOP in other languages can be obtained under: www.dop.ravatherm.com

