

<b>1. Unique identification code of the product-type:</b> <b>RAVATHERM XPS X ULTRA 300 SL</b>	
< 80 mm    XPS - EN13164 - T1 - CS(10Y)300 - CC(2/1,5/50)110 - DS(70,90) - DLT(2)5 - WD(V)2 - WL(T)0,7 - FTCD1 80mm ≤ d ≤ 120mm    XPS - EN13164 - T1 - CS(10Y)300 - CC(2/1,5/50)110 - DS(70,90) - DLT(2)5 - WD(V)1 - WL(T)0,7 - FTCD1 ≥125mm    XPS - EN13164 - T1 - CS(10Y)300 - CC(2/1,5/50)110 - DS(70,90) - DLT(2)5 - WD(V)1 - WL(T)0,7 - FTCD1 – TR200	
2. Intended use/es:	Thermal Insulation for Buildings (ThIB)
3. Manufacturer:	<b>Ravago Building Solutions S.A.</b> 2146 Luxembourg, 76-78 Rue de Merl
4. Authorized representative:	-
5. System/s of AV/CP:	System 3
6a. Harmonised standard:	EN 13164:2012+A1:2015
Notified body/ies:	FIW (0751) - LNE (0071) - CSTB (0679) - ÉMI (1415) - OFI (1085)

7. Declared performance/s:		
Essential characteristic	Symbol	Performance
Thermal conductivity		
	$\lambda_d$	0,027
Thermal resistance	$R_d$	*
Dimensional tolerances	T	T1
Compressive strength	CS(10Y)	300
Tensile strength perpendicular to faces	125 mm ≥ d TR	200
Reaction to fire	RfF	E
Continuous glowing combustion		NPD
Long term water absorption by total immersion	WL(T)	0,7
Long term water absorption by diffusion	<80 mm	2
	80 – 205 mm	1
Water vapor diffusion resistance factor	MU	NPD
Durability of compressive strength against (compressive creep)	CC (2/1,5/50)	110
Durability of reaction to fire against heat, weathering, ageing/degradation	No change in reaction to fire properties for extruded polystyrene foam	
Durability of thermal resistance against heat, weathering, ageing/degradation		
Thermal resistance and thermal conductivity	see above $R_d$ and $\lambda_d$	
Freeze/thaw resistance after long term water absorption by diffusion	FTCD	1
Dimensional stability under specified temperature and humidity conditions	DS	(70,90)
Deformation under specified compressive load and temperature conditions	DLT	(2) 5
Release of dangerous substances to the indoor environment		NPD

\* Thermal resistance ( $R_d$ )

Thickness	$R_d$ (m <sup>2</sup> K/W)	Thickness	$R_d$ (m <sup>2</sup> K/W)	Thickness	$R_d$ (m <sup>2</sup> K/W)
70 mm	2.60	130 mm	4.80	180 mm	6.65
80 mm	2.95	140 mm	5.15	200 mm	7.40
100 mm	3.70	145 mm	5.35	205 mm	7.55
105 mm	3.85	160 mm	5.90		
120 mm	4.40	175 mm	6.45		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Stijn de Vry, Business Director

Place and date of issue:

2146 Luxembourg, 2026.05.12

Signature



NPD – No Performance Determined

Ravatherm XPS X ULTRA 300 SL DoP Version 3 20260625



Note: DOP in other languages can be obtained under: [www.dop.ravatherm.com](http://www.dop.ravatherm.com)